

# PARTNER

CARE . TRUST . RESPONSIBILITY

## CLEO

### AII-IN-ONE COMPACT POS



#### Not Just a Pretty Face!

Packed with power, the Cleo C10/ C14 POS delivers top performance in a compact, minimalistic design, elevating the checkout experience in retail and hospitality.

Built on the latest technology that supports new, more demanding applications and databases. The Intel Elkhart Lake/Rockchip RK3568 processor, M.2 SSD memory and up to 16 GB DDR4 RAM ensure high-speed data processing and responsiveness in all situations.

The Cleo C10/C14 is specially designed for counter-limited industries. The compact design helps conserve counter space with its small footprint, and because peripherals are integrated into the all-in-one, it keeps workspaces uncluttered.

#### SPECIAL FEATURES

- Compact design with small footprint
- Integrated built-in 80mm thermal printer
- Extremely small footprint

#### OPTIONS

- 10.1" customer display with or without touch
- 3-track magnetic card reader chip card reader
- NFC/RFID Reader
- Fingerprint Sensor

**CLEO**

MODELL	CLEO-1E	CLEO-1R
Display	10.1", Resolution 800 x 1280 (250 nits) 14", Resolution 1366 x 768 (220 nits)	
Touch	PCAP touch	
CPU	Intel®Celeron®Processor J6412 (Elkhart Lake)	Rockchip RK3568
Memory	DDR4 4GB, 8GB, 16GB	DDR4 4GB
Storage	M.2PCIeSSD:128GB/256GB/512GB	eMMC 64GB + 1x Micro SD Card Slot
External I/O Interface	4 x USB 3.2 + 2 x USB 2.0	
	4 x Serial ports, RS232 (RJ45), 0V/5V/12V selected in BIOS (COM1, COM2, COM3, COM4)	4 x Serial Ports, RS232 (RJ45), 0V/5V/12V Selection by UI (COM1, COM2, COM3, COM4)
	1 x LAN (IEEE802.310/100/1000 Mbps Ethernet, RJ45)	
	1 x RJ11 port supports 2 Cash drawers with 24V / 12V by jumper setting	
	1 x Audio (1 x line out)	
	1 x HDMI 2.1	
	1 x DC + 24V input	
		N/A
Speaker	1 x Speaker (3W)	
Printer	3" Thermal printer	
Optional Peripheral	MSR(Beep), IC Card Reader, Fingerprint, RFID	
	2D Barcode Scanner	
	5MP Camera	
	USB 2nd Display	
WIFI/BT (Option)	IEEE 802.11 a/b/g/n/acR2/axR2, BT 5.2	IEEE 802.11 a/b/g/n/ac/ax , BT 5.0 (on board)
Display Support	3 Independent Displays (Main Display + HDMI + CD-101C)	2 Independent Displays (Main Display + CD-101C or HDMI)
Spill & Dust resistant	N/A	

**CLEO**

MODELL	CLEO-1E	CLEO-1R
Operation System	1. Windows 11 IoT Enterprise AC (64bit)	Android 12
	2. Windows 10 IoT Enterprise LTSC 21H2 (64bit) and newer version	
	3. Linux (Ubuntu 22.04)	
TPM	H/W TPM 2.0	N/A
Power Adaptor	AC-In 100~240V / DC-Out 24V,72W	
Reliability	System Operating Temperature:0~40°C (32~104°F)	
	System Humidity: 15% ~ 80%	
	Storage Temperature: -20~60°C (-4~140°F)	
Dimensions (Wx Hx D)	262.26(B)x291.77(H)x247.13(T)mm/10.33(B)x11.49(H)x9.73(T)inch	
Weight	3.3 Kgs / 7.28 lbs	

\*Specification is subject of change without prior notice. Mar23

